



TAMBURO 16

SEMI-FLUSH MOUNT CEILING

location:
DAMP

SPECIFICATIONS:

DESCRIPTION

Semi-flush mounted ceiling luminaires, featuring handcrafted glass. "Near Ceiling" design creates soft ceiling glow.

LAMPING

Standard: 3x60W A19 120V incandescent, lamp not included. Dimmable with standard incandescent dimmer (not included).

CFL: Standard 4-Pin CFL with non-dimming electronic ballast. 120V, lamp not included.

GU24 CFL: Self-ballasted GU24 lampholders. 26W max, 120V, lamp not included.

LED: 3x11W Replaceable LED source, 120V, dimmable, 80+ CRI, 2800°K CCT, 1100 lumens, 30,000 hours. Lamp included.

DIFFUSER

Handcrafted glass diffuser is available in various decors. 15.75" Dia. x 8" H

CONSTRUCTION

Canopy (5" dia.) is plated stamped steel. Canopy and glass retainer hardware are available in either Bronze or Satin Nickel finish.

MOUNTING


Installs directly to a 4" octagonal outlet box, centered on fixture. 90°C supply wire required for incandescent lamping.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



TAMBURO 16 CEILING SHOWN IN GLITTER STONE (4008GL)



4008GS
STONE GOLD FOIL



4008CS
STONE COPPER FOIL



4008SS
STONE SILVER FOIL



400800
CLEAR STONE




400807
OPAL MATTE



4008KR
CHALK



4008TN
TITAN



4008OK
OAK



4008CH
CHERRY



For ordering information, see next page

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 1/17



ORDERING:

FIXTURE	GLASS OPTIONS	LAMP OPTIONS	METAL FINISH	OPTIONS
1KM Ceiling	400807 Opal Matte	(blank) 3x 60W A19 Incan	BR Bronze	LW Low Wattage
	4008CH Cherry	I3 3x 26W TBX 120V	SN Satin Nickel	labeling
	4008KR Chalk	R3 3x 26W TBX 277V		
	4008OK Oak	GU24 3x 26W GU24		
	4008TN Titan	LED 3x 11W LED 120V, dimmable		
	400800 Clear Stone			
	4008CS Stone Copper Foil			
	4008GL Glitter Stone			
	4008GS Stone Gold Foil			
	4008SS Stone Silver Foil			

Project Information: